Shuttle®

xPC SN27P2 AMD Athlon™ 64/X2/FX

Supports AMD
Socket AM2
DDR2 Memory

FEATURES

- AMD Sempron/Athlon™ 64 / X2 / FX Processor Ready (Socket AM2)
- 1 GHz HyperTransport Technology
- DDR2 667/800 Dual Channel Support
- 4 x 240 pin DDR2 DIMM Slots - 2GB per Slot (Max. 8GB)
- Full Featured PCI Express x16 Slot
- SATA 3Gb/s with RAID Controller
- UltraDMA 133 Master Mode Parallel ATA Controller
- Gigabit Ethernet
- High-performance audio 90dB Playback SNR quality
- Silent X 400W Power Supply

We create!

SPECIFICATIONS

FORM FACTOR
· Shuttle Form Factor
· P2 Chassis

PROCESSOR
· AMD Sempron/Athlon™ 64/FX/X2 Processor
· Socket AM2

CHIPSET
· NVIDIA nForce® 570 MCP

MEMORY
· 4 x 240 pin DDR2 DIMM Slots
· 2GB per Slot (Max. 8GB)
· Support DDR2 667/800 Dual Channel Unbuffered RAM

ATA
· SATA 3Gb/s with RAID 0, 1, 0+1, 5, JBOD
· ATA UltraDMA-133

AUDIO
· Realtek ALC882 HD Audio
· 7.1 + 2 HD Channels
· Above 103dB SNR quality output

ETHERNET
· Marvell 88E1116 Gbit LAN PHY
· Supports 10/100/1000 Mbps Operation
· Supports power saving mode
· NVIDIA Firewall included
· Support for IPv4 and IPv6

IEEE1394a
· VIA VT6307 Controller
· IEEE1394 OHCI V1.0 Compliant
· 400/200/100 Mb/s Data Transfer Rate

ONBOARD HEADERS & CONNECTORS
· (4) 4-pin Fan Connectors
· (1) ATX Main Power Connector
· (1) 12V Power Connector
· (3) SATA Connector
· (1) ATA133 IDE Connector
· (1) Floppy Connector
· (1) AUX In Connector
· (2) 1x5 Pin USB 2.0 Header
· (1) Front Panel Connector
· (1) Front Panel Header

FRONT PANEL
· (2) USB 2.0 Ports
· (1) Mini IEEE1394 Port
· (1) Mic In
· (1) Earphone Out
· (1) Power on Button
· (1) Reset Button
· (1) HDD LED
· (1) Power LED

BACK PANEL
· (1) PCI Express x16 Slot
· (1) PCI Slot
· (6) USB 2.0 Ports
· (1) RJ45 10/100/1000 Mbps LAN Port
· (1) IEEE1394a Port
· (1) External SATA Port
· (1) Front Out
· (1) Side Surround Out
· (1) Rear Out
· (1) Center/Bass Out
· (1) S/PDIF Coaxial Out
· (1) S/PDIF Optical In
· (1) S/PDIF Optical Out
· (1) Clear CMOS Button
· (1) WLAN Hole for PN18 (Optional)

EXPANSION BAY
· (1) 3.5" Bay
· (2) 3.5" Bays (Internal)
· (1) 5.25" Bay

DIMENSIONS
· 325(L) x 220(W) x 210(H) mm

POWER
· Silent X 400W(PFC) Power Supply Unit
· Input 100-240V AC

ACCESSORIES
· (1) XPC Multi-Language User Guide
· (1) XPC CD 32bit Driver
· (1) XPC CD 64bit Driver
· (1) Shuttle Extras CD
· (1) RAID Installation Guide
· (1) RAID Floppy Disk
· (1) ICE CPU Heat-pipe
· (1) IDE ATA133 Cable
· (1) FDD Cable
· (1) Power Cord
· (1) SATA Cable
· (1) Screws Pack
· (1) Heatsink Compound

Shuttle Inc.® 2006, All Rights Reserved.
* All other brand and product names within this page are the property of their respective owners.
* The specification is subject to change without further notice.